



SPLIT CASSETTE

Inverter - Frío/Calor

16 SEER

Split Cassette Inverter R410A

FRÍO/CALOR - 16 SEER



Frío/Calor

Evaporadora			LICH4024160U432	LICH4036160U432	LICH4048160U432	LICH4060160U432
Condensadora			LISH024000U432	LISH036000U432	LISH048000U432	LISH060000K432
Enfriamiento	Capacidad Nominal	Btu/h	23800	34500	47800	52500
	EER	w/w	3.21	2.97	2.59	2.78
	SEER		16	16	16	16
Calefacción	Capacidad Nominal	Btu/h	27200	37500	51200	58000
	HSPF		9	9	9	9
Alimentación Eléctrica		V/Hz/Ph	220-240V/1Ph/50-60Hz			
Salida de potencia		W	35	35	150	150
Amperaje		FLA	27	44	8	8
Flujo de volumen de aire	Turbo	CFM	735	883	1059	1177
	Alta	CFM	674	853	1000	1118
	Media	CFM	559	795	883	942
	Baja	CFM	500	706	765	824
Dimensiones	Alto	mm.	200	238	290	290
	Ancho	mm.	840	840	840	840
	Profundo	mm.	840	840	840	840
Nivel de presión sonido	Turbo	dB(A)	47	50	51	54
	Alta	dB(A)	45	48	49	52
	Media	dB(A)	41	46	46	50
	Baja	dB(A)	39	42	42	48
Peso neto		kg.	30	38	41	44
Peso de envío		kg.	23	31	33	36
Alimentación Eléctrica			220-240V/1Ph/50-60Hz			
Compresor	Tipo		Rotary	Rotary	Rotary	Rotary
	Cantidad	Núm	1	1	1	1
	RLA	A	11	11	19.7	19.7
Motor de ventilador externo FLA		A	7	89	1.38	1.38
Flujo de volumen de aire		CFM	2119	2354	3472	3472
Nivel de presión de sonido		dB(A)	56	55	59	60
Dimensiones	Alto	mm.	698	790	820	820
	Ancho	mm.	891	919	939	939
	Profundo	mm.	340	371	459	459
Peso neto		kg.	52.8	60.8	91.8	96
Peso con embalaje		kg.	56.8	65.8	103.8	108
Tipo de refrigerante			R410A	R410A	R410A	R410A
Carga de refrigerante		kg.	1.99	2.44	3.69	3.79
Conexión		%	100	100	100	100
Max. Unidades Internas		Núm.	1	1	1	1
Temperatura de operación	Enfriamiento	°F (°C)	5(-15) - 118(48)	5(-15) - 118(48)	5(-15) - 118(48)	5(-15) - 118(48)
	Calefacción	°F (°C)	5(-15) - 75(24)	5(-15) - 75(24)	5(-15) - 75(24)	5(-15) - 75(24)
Max. tiro de tuberías pies		m.	50	50	75	75
Unidad Externa Debajo/Arriba Pies		m.	25	25	30	30
Tubería de conexión	Lado Líquido	mm(Inch)	φ9.5(φ3/8)	φ9.5(φ3/8)	φ9.5(φ3/8)	φ9.5(φ3/8)
	Lado Gaseoso	mm(Inch)	φ16(φ5/8)	φ16(φ5/8)	φ16(φ5/8)	φ16(φ5/8)
Control Remoto	Voltaje suministro	AAA	2	2	2	2
	Rango de trabajo	°F (°C)	61(16) - 86(30)	61(16) - 86(30)	61(16) - 86(30)	61(16) - 86(30)
	Rango de recepción	m.	8	8	8	8