



NUEVO  
MINI-SPLIT

16 SEER



SPLIT PARED INVERTER

Frío Solo - Frío/Calor

# Split Pared Inverter R410A



## Frío Solo

| Evaporadora            |                                                          |          | LI012CI-160P433     | LI018CI-160P433     | LI024CI-160P433    |
|------------------------|----------------------------------------------------------|----------|---------------------|---------------------|--------------------|
| Condensadora           |                                                          |          | LI012CO-160P433     | LI018CO-160P433     | LI024CO-160P433    |
| Alimentación Eléctrica |                                                          | V/Hz/Ph  | 208-230/60/1        | 208-230/60/1        | 208-230/60/1       |
| Enfriamiento           | Capacidad Neta                                           | Btu/h    | 11307               | 16548               | 22519              |
|                        | EER                                                      | W        | 2.80                | 2.84                | 2.83               |
|                        | SEER                                                     |          | 16.5                | 17.5                | 16.6               |
| Evaporadora            | Salida de potencia                                       | W        | 14                  | 25                  | 45                 |
|                        | Amperios de carga nominal                                | RLA      | 0.19                | 0.12                | 0.2                |
|                        | Flujo de volumen de aire                                 | CFM      | 294/241/188         | 441/353/317         | 765/706/588        |
|                        | Dimensiones                                              | mm.      | 203×787×254         | 203×914×305         | 229×1016×305       |
|                        | Nivel de presión sonido                                  | dB(A)    | 38/34/30            | 43/38/34            | 49/45/41           |
|                        | Peso neto                                                | kg.      | 8.16                | 9.97                | 13.15              |
|                        | Peso de envío                                            | kg.      | 9.97                | 13.15               | 15.87              |
|                        | Compressor                                               | Tipo     | Rotary              | Rotary              | Rotary             |
| Condensadora           |                                                          | RLA      | A                   | 5.65                | 6.8                |
|                        | Motor de ventilador exterior RLA                         | A        | 0.15                | 0.15                | 0.15               |
|                        | Flujo de volumen de aire                                 | CFM      | 1136                | 1448                | 1448               |
|                        | Nivel de presión de sonido                               | dB(A)    | 52                  | 54                  | 52                 |
|                        | Dimensiones                                              | mm.      | 508×787×279         | 610×864×356         | 610×864×356        |
|                        | Peso neto/bruto                                          | kg.      | 20.86               | 29.93               | 29.93              |
|                        | Temperatura de operación                                 | °F (°C)  | 64(18) - 114(43)    | 64(18) - 109(43)    | 64(18) - 109(43)   |
|                        | Tipo de refrigerante                                     | kg.      | R410A/ 0.53         | R410A/0.68          | R410A/0.98         |
| Tubería de conexión    | Lado líquido / Lado gas                                  | mm(Inch) | φ6(φ1/4)+φ9.5(φ3/8) | φ6(φ1/4)+φ9.5(φ3/8) | φ6(φ1/4)+φ12(φ1/2) |
|                        | Longitud máxima de distancia/ Altura máxima de distancia | m.       | 10/5                | 15/5                | 15/5               |

## Frío/Calor

| Evaporadora            |                                                          |              | LI012HI-160P433     | LI018HI-160P433     | LI024HI-160P433    |
|------------------------|----------------------------------------------------------|--------------|---------------------|---------------------|--------------------|
| Condensadora           |                                                          |              | LI012HO-160P433     | LI018HO-160P433     | LI024HO-160P433    |
| Alimentación Eléctrica |                                                          | V/Hz/Ph      | 208-230/60/1        | 208-230/60/1        | 208-230/60/1       |
| Enfriamiento           | Capacidad Neta                                           | Btu/h        | 10918               | 16412               | 22007              |
|                        | EER                                                      | W            | 2.80                | 2.82                | 2.82               |
|                        | SEER                                                     |              | 16.5                | 17.5                | 16.6               |
| Calefacción            | Capacidad Neta                                           | Btu/h        | 11505               | 17183               | 21376              |
|                        | COP                                                      |              | 3.01                | 3.07                | 2.81               |
| Evaporadora            | Salida de potencia                                       | W            | 14                  | 25                  | 45                 |
|                        | Amperios de carga nominal                                | RLA          | 0.17                | 0.12                | 0.2                |
|                        | Flujo de volumen de aire                                 | CFM          | 294/241/188         | 441/353/317         | 588/541/418        |
|                        | Dimensiones                                              | mm.          | 203×787×254         | 203×914×305         | 229×1016×305       |
|                        | Nivel de presión sonido                                  | dB(A)        | 38/34/30            | 43/38/34            | 49/45/41           |
|                        | Peso neto                                                | kg.          | 8.1                 | 9.97                | 13.15              |
|                        | Peso de envío                                            | kg.          | 9.97                | 13.15               | 15.87              |
|                        | Compressor                                               | Tipo         | Rotary              | Rotary              | Rotary             |
| Condensadora           |                                                          | RLA          | A                   | 5.65                | 6.8                |
|                        | Motor de ventilador exterior RLA                         | A            | 0.15                | 0.15                | 0.15               |
|                        | Flujo de volumen de aire                                 | CFM          | 1136                | 1448                | 1448               |
|                        | Nivel de presión de sonido                               | dB(A)        | 52                  | 54                  | 55                 |
|                        | Dimensiones                                              | mm.          | 508×787×279         | 610×864×356         | 610×864×356        |
|                        | Peso neto/bruto                                          | kg.          | 22.2                | 30.8                | 33.11              |
|                        | Temperatura de operación                                 | Enfriamiento | °F (°C)             | 64(18) - 109(43)    | 64(18) - 109(43)   |
|                        |                                                          | Calefacción  | °F (°C)             | 19.4(-7) - 88(31)   | 19.4(-7) - 88(31)  |
| Tipo de refrigerante   |                                                          | kg.          | R410A/ 0.58         | R410A/1.06          | R410A/1.38         |
| Tubería de conexión    | Lado líquido / Lado gas                                  | mm(Inch)     | φ6(φ1/4)+φ9.5(φ3/8) | φ6(φ1/4)+φ9.5(φ3/8) | φ6(φ1/4)+φ12(φ1/2) |
|                        | Longitud máxima de distancia/ Altura máxima de distancia | m.           | 10/5                | 15/5                | 15/5               |